



A




B



E




F



G



H



## A JOINT

Splices poles easily and securely with 6 ft. sections to achieve total desired height. Three separate safety stops. Works well with all pole lengths.

**AP6J**

## B ALUM-A-POLE

All weather structural aluminum and Saf-T-Grip rubber exceeds OSHA standards. Poles can be spliced to 50' maximum shoulder working length. Lifetime non-slip, non-wear replacement warranty.

6' Pole – **AP6P**

12' Pole – **AP12P**

18' Pole – **AP18P**

24' Pole – **AP24P**

## C END RAIL NET SYSTEM 14"

Protects materials or users from falling

**APSER**

## D SAF-T-NET 22'

Falling to the ground scaffolding hazards are virtually eliminated because Saf-T-Net moves up and down with the worker.

**APSNET**

## E SCAFFOLDING

5-1/4" rail 500 lb. rating. An infinitely joinable, non-overlapping walkway. Accepts Pro-Jack Saf-T-Lok Chain for protection from twist-out and upending. Designed for superior strength and traction. Large drain holes for rain and snow. Exclusive design provides minimal ice build-up

14" x 16' – **APSCAFF1416**

14" x 24' – **APSCAFF1424**

20" x 14' – **APSCAFF2014**

20" x 20' – **APSCAFF2020**

20" x 24' – **APSCAFF2024**

24" x 24' – **APSCAFF2424**

## F BRACE

Folding model secures scaffolding to structure quickly and easily. Multi-angle swivel provides flexibility for mid-bracing on total structure. Universal joint fits any roof.

Foldable – **APBRAFF**

Rigid – **APBRAR** (NOT SHOWN)

## G PRO-JACK

4,000 lb. tested telescopic pump-jack with safety features and a self-storing Saf-T Crank handle. Built-in Saf-T-Lok Chain. Secures staging too.

**APPROJ**

## H PRO-BENCH

A telescoping aluminum workbench and guard rail combination. Up to 27" wide staging capacity. Built-in Saf-T-Lok Chain. Provides anti-theft and greater safety.

**APPROB**

**A WERNER STAGES**

Vinyl-coated end caps, double end rung on stages 20' or longer, Twist-Proof® Stage Design.

**ONE PERSON STAGE, 250 LB. RATING**

- 12" x 16' – 2016
- 12" x 20' – 2020
- 12" x 24' – 2024

**TWO PERSON STAGE, 500 LB. RATING**

- 12" x 16' – 2316
- 12" x 20' – 2320
- 12" x 24' – 2324
- 14" x 16' – 2416
- 14" x 20' – 2420
- 14" x 24' – 2424
- 20" x 24' – 2524



**B WERNER WIDE SPAN ALUM SCAFF TOWER**

10' L x 4'6" W x 23' H 4203-23  
4203-23

**C WERNER PORTABLE SCAFFOLD 500 LB**

46" W x 24" D x 50" H  
PS-48

**D WERNER ALUM WORK PLATFORM 225 LB**

17" W x 36" D x 41" H  
AP-20-MP6

**E WERNER ALUM PORTABLE WORK STAND 300LB**

3'  
TW37330

