



ROOFERS FALL KIT (IN A BUCKET)

Kit includes 1 each of the following: Full-body harness, combination rope grab and shock absorber, 5/8"x50' rope lifeline with attached double locking snaphook, reusable galvanized roof anchor bracket.

BT3713



DBI ECONOMY ROOFER KIT

Kit includes 1 each of the following: Full-body harness, combination rope grab and shock absorber, 5/8"x50' rope lifeline with attached double locking snaphook, 2 each non-reusable roof anchor brackets.

BT3765 (NOT SHOWN)

DBI "LIGHT" COMPLIANCE IN A CAN, HARNESS AND LAYNARD ONLY AA7010AS

BT3753 (NOT SHOWN)

FULL BODY HARNESS LARGE

Lightweight, sub-pelvic, polyester full-body harness. Infinitely adjustable parachute buckles on the leg straps and quick connect chest strap

Size: Standard - **BT3707**

Size: XL - **BT3741 (NOT SHOWN)**



AUTO ROPE GRAB 5/8" LIFELINE

Automatic energy absorbing rope grab follows a worker up and down a 5/8"- 3/4" diameter vertical synthetic lifeline. The unit's controlled, shock-absorbing action eliminates the need for an energy absorbing lanyard. Allows the rope grab to be attached, detached and positioned at any point on the vertical lifeline. Weighs 1-1/2 lbs. and is made of stainless steel.

BT3704



WEB LANYARD WITH SHOCK ABSORBER

Soft-Pack energy absorber with 1" wide polyester web lanyard with a locking snaphook at each end.

3' - **BT3701**

6' - **BT3702 (NOT SHOWN)**



ROPE LANYARD 5/8" DIAM. WITH SNAPHOOK

A locking snaphook spliced to one end only, perfect for use as a lifeline.

25' - **BT3400**

50' - **BT3401 (NOT SHOWN)**



HEAVY DUTY HINGED REUSABLE ROOF ANCHOR

Rated at 5,000 lb. Reusable Hinge-style 11 gauge zinc-plated steel. Attaches to the roof using 16d (penny) double-headed nails or #8 x 3-1/2" long wood screws. Anchor is designed to be removed when the job is complete and reused after inspection. OSHA-compliant anchorage point capable of supporting 5,000 lbs.

BT3703



DBI U-BOLT ROOF ANCHOR

Perm. roof anchor for open trusses, joists and rafters. Integral D-ring anchorage point. Weather tight cap protects the anchor from corrosion and hides the anchor. Thermoplastic flashing. Fits up to 2x8 roof truss, joist or rafter. 5,000 lb. rated.

BT3735



DBI DELTA2 BODY HARNESS CONSTRUCTION VEST STYLE WITH BACK D-RING 1103513

BT3744



DBI EXOFIT BODY HARNESS VEST STYLE 1110103

With padding, quick connect buckles, and stand up back D-ring.

BT3745

